


DL 3806 LED



Colour(s)



142x142 mm



DOWNLIGHTS ■ LED

- Square recessed low luminance downlight for LED DOWNLIGHT module, maximum 5 000 lumens
- CRI of 80
- MacAdam Ellipse : 3 SDCM
- High output reflector, made of Miro 4 Silver aluminium
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L70B50)
- Luminous efficiency of system up to 90 lm/W
- Springs in pressure for easier installation
- Housing made of die-cast alloy
- Static heat sink made of die-cast aluminium
- **Weight:** 1,5 kg
- **Driver(s):** Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD), Safety glass IP 44

Driver(s)




Standards

Class I | IP 20 | 650°

Beam(s)



Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
DL 3806 LED 1100-830	12,5W	14W	1100 lumens	80 lm/W	3000 K	80	E
DL 3806 LED 1100-840	11W	12,5W	1100 lumens	89,5 lm/W	4000 K	80	D
DL 3806 LED 2000-830	22W	24,5W	2000 lumens	81 lm/W	3000 K	80	E
DL 3806 LED 2000-840	20W	22,5W	2000 lumens	89,5 lm/W	4000 K	80	D
DL 3806 LED 3000-830	33W	37W	3000 lumens	81,5 lm/W	3000 K	80	E
DL 3806 LED 3000-840	30W	33,5W	3000 lumens	90 lm/W	4000 K	80	D
DL 3806 LED 5000-830	56W	62W	5000 lumens	80,5 lm/W	3000 K	80	E
DL 3806 LED 5000-840	50,5W	56,5W	5000 lumens	89 lm/W	4000 K	80	D