

EO 2241-B LED



Colour(s)



Ø153 mm



ORIENTABLE AND ADJUSTABLE ■ LED

- Circular recessed orientable spotlight for LED SPOT module, maximum 4 500 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 2 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- luminous efficiency of system up to 151,2 lm/W
- Springs in pressure for easier installation
- Ring made of die-cast aluminium
- Static heat sink
- **Weight:** Approx. 1,8 kg
- **Driver(s):** Fixe (C Fixed), Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD)

Driver(s)



Standards

Class I | IP 20 | 650°



Efficiency energy class



Beam(s)



Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
EO 2241-B LED 2500-930	19W	21W	2425 lumens	115,5 lm/W	3000 K	90
EO 2241-B LED 2500-940	19W	21W	2725 lumens	129,7 lm/W	4000 K	90
EO 2241-B LED 3000-830	19W	21W	3025 lumens	144 lm/W	3000 K	80
EO 2241-B LED 3000-840	19W	21W	3175 lumens	151,2 lm/W	4000 K	80
EO 2241-B LED 3500-930	31W	34W	3450 lumens	101,5 lm/W	3000 K	90
EO 2241-B LED 3500-940	31W	34W	3850 lumens	113,2 lm/W	4000 K	90
EO 2241-B LED 4000-830	31W	34W	4275 lumens	125,7 lm/W	3000 K	80
EO 2241-B LED 4000-840	31W	34W	4500 lumens	132,3 lm/W	4000 K	80