

■ LC 3890 LED



Colour(s)

CONTINUOUS ROWS ■ LED

- Suspended continuous row lighting which can receive 1, 2, 3 or 4 recessed luminaires
- CRI of 80 and 90
- MacAdam Ellipse: 3 SDCM
- Endcap, screen suspension bracket and junction plate available in accessories
- Housing made of prelacquered steel
- Prewiring 3 x 1,5 mm<sup>2</sup>
- **Weight:** 5 kg (1000 mm), 10 kg (2000 mm)
- **Number of recessed luminaires:** 1, 2, 3 or 4
- **Standard lengths:** 1 000 mm or 2 000 mm

Driver(s)

FIXED

C  
DIMM  
DALI

Standards

Class I | IP 20 | 650°

Beam(s)

16,5°

33°

42°

59°

Dimensions

68 mm

225 mm

1 000 ou 2 000 mm

■ TRUNKING WITH ORIENTABLE & ADJUSTABLE EO 5056-A LED D120

| ITEM                        | SECTION  | POWER  | CONSUMPTION | LUMINOUS FLUX | SYSTEM EFFICIENCY | COLOUR TEMPERATURE | CRI | EFFICIENCY ENERGY CLASS |
|-----------------------------|----------|--------|-------------|---------------|-------------------|--------------------|-----|-------------------------|
| EO 5056-A LED D120 2000-925 | Bakery   | 23,7 W | 26,9 W      | 2171 lumens   | 80,7 lm/W         | 2500 K             | 90  | E                       |
| EO 5056-A LED D120 2000-930 | Butchery | 23,7 W | 26,9 W      | 2297 lumens   | 85,4 lm/W         | 3000 K             | 90  | E                       |
| EO 5056-A LED D120 3300-930 | -        | 23,8 W | 27,1 W      | 3281 lumens   | 121 lm/W          | 3000 K             | 90  | E                       |
| EO 5056-A LED D120 3400-940 | -        | 23,8 W | 27,1 W      | 3384 lumens   | 125 lm/W          | 4000 K             | 90  | E                       |
| EO 5056-A LED D120 3700-830 | -        | 23,8 W | 27,1 W      | 3684 lumens   | 136 lm/W          | 3000 K             | 90  | D                       |
| EO 5056-A LED D120 3900-840 | -        | 23,8 W | 27,1 W      | 3949 lumens   | 145,5 lm/W        | 4000 K             | 80  | D                       |

■ **LC 3890 LED**

length 1 000 mm




1 x EO 5056-A LED D120



2 x EO 5056-A LED D120


length 2 000 mm




1 x EO 5056-A LED D120



2 x EO 5056-A LED D120




3 x EO 5056-A LED D120




4 x EO 5056-A LED D120


**Accessories**



Endcap



Screen suspension bracket



Junction plate

■ **EXAMPLES OF OTHER INTEGRABLE PRODUCTS**

**Orientable and adjustable**



EO 2225 LED



EO 5056-B LED



EO 2242 LED

**DOWNLIGHTS**



DL 2180 LED



DL 3806 LED