

EO 2241-A LED



Colour(s)



ORIENTABLE AND ADJUSTABLE - LED

- Circular recessed orientable spotlight for LED SPOT module, maximum 7 700 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 151,2 lm/W
- Springs in pressure for easier installation
- Ring made of die-cast aluminium
- Static heat sink
- **Weight:** Approx. 1,8 kg
- **Driver(s):** Fixe (C Fixed), Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD), Colour filters (FIL)

Driver(s)



Standards

Classe I | IP 20 | 650°


Efficiency energy class



Beam(s)



Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
EO 2241-A 3000-830	19W	21W	3025 lumens	144 lm/W	3000 K	80
EO 2241-A 3000-840	19W	21W	3175 lumens	151,2 lm/W	4000 K	80
EO 2241-A 3500-930	31W	34W	3450 lumens	101,5 lm/W	3000 K	90
EO 2241-A 3500-940	31W	34W	3850 lumens	113,2 lm/W	4000 K	90
EO 2241-A 4500-830	31W	34W	3275 lumens	96,3 lm/W	3000 K	80
EO 2241-A 4500-840	31W	34W	4500 lumens	132,3 lm/W	4000 K	80
EO 2241-A 4500-930	39W	43W	4150 lumens	96,5 lm/W	3000 K	90
EO 2241-A 4500-940	39W	43W	4575 lumens	106,4 lm/W	4000 K	90
EO 2241-A 5000-830	39W	43W	5075 lumens	118 lm/W	3000 K	80
EO 2241-A 5000-840	39W	43W	5350 lumens	124,4 lm/W	4000 K	80
EO 2241-A 7500-830	49W	55W	7325 lumens	133 lm/W	3000 K	80
EO 2241-A 7500-840	49W	55W	7700 lumens	140 lm/W	4000 K	80