

■ LS 2241 LED



Colour(s)

SUSPENDED LUMINAIRES ■ LED

- Suspended luminaire which can receive 4 recessed orientable spotlight for LED SPOT module, 4 x 7 700 lumens maximum
- CRI of 80 or 90
- MacAdam Ellipse : 2 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B50)
- Luminous efficiency of system up to 151,2 lm/W
- Housing made of lacquered steel
- Suspension by steel wire
- **Weight:** approx. 12 kg
- **Driver(s):** Fixe (C Fixed), Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD)

Driver(s)

C
FIXED

C
DIMM
DALI

Standards

Class I | IP 20 | 650°

Beam(s)

10°

24°

30°

50°

20°

40°

60°

A

B

Dimensions

125 mm

595 mm

595 mm

595 mm

ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	BEAM(S)	EFFICIENCY ENERGY CLASS
LS 2241 LED 3000-830	4x19W	4x21W	4x3025 lumens	144 lm/W	3000 K	80	A	D
LS 2241 LED 3000-840	4x19W	4x21W	4x3175 lumens	151,2 lm/W	4000 K	80	A	D
LS 2241 LED 3500-930	4x31W	4x34W	4x3450 lumens	101,5 lm/W	3000 K	90	A	E
LS 2241 LED 3500-940	4x31W	4x34W	4x3850 lumens	113,2 lm/W	4000 K	90	A	E
LS 2241 LED 4500-830	4x31W	4x34W	4x4275 lumens	125,7 lm/W	3000 K	80	A	D
LS 2241 LED 4500-840	4x31W	4x34W	4x4500 lumens	132,3 lm/W	4000 K	80	A	D
LS 2241 LED 4500-930	4x39W	4x43W	4x4150 lumens	96,5 lm/W	3000 K	90	A	E
LS 2241 LED 4500-940	4x39W	4x43W	4x4575 lumens	106,4 lm/W	4000 K	90	A	E
LS 2241 LED 5000-830	4x39W	4x43W	4x5075 lumens	118 lm/W	3000 K	80	A	D
LS 2241 LED 5000-840	4x39W	4x43W	4x5350 lumens	124,4 lm/W	4000 K	80	A	D
LS 2241 LED 7500-830	4x49W	4x55W	4x7325 lumens	133 lm/W	3000 K	80	B	D
LS 2241 LED 7500-840	4x49W	4x55W	4x7700 lumens	140 lm/W	4000 K	80	B	D