



- Circular recessed low luminance downlight for LED DOWNLIGHT module, maximum 7 700 lumens
- CRI of 80 and 90
- MacAdam Ellipse : 2 SDCM
- High output reflector, made of faceted anodized aluminium (FAC)
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 166,6 lm/W
- Springs in pressure for easier installation
- Housing and ring made of powder die-cast aluminium
- Static heat sink made of die-cast aluminium
- **Weight** : 1 kg
- **Driver(s)** : Fixed, Dimmable DALI (CDIMMDALI)
- **Option(s)** : Fast connector (CORD)

Driver(s)




Standards

Class I | IP 20 | 650°

Beam(s)



Dimensions



Colour(s)



Ø155 mm



ITEM	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	BEAM	EFFICIENCY ENERGY CLASS
DL 2126 LED-2000-930	14W	1918 lumens	137,9 lm/W	3000 K	90	B	D
DL 2126 LED-2000-940	14W	2016 lumens	145 lm/W	4000 K	90	B	D
DL 2126 LED 3000-830	21W	3025 lumens	144 lm/W	3000 K	80	B	D
DL 2126 LED 3000-840	21W	3175 lumens	151,2 lm/W	4000 K	80	B	D
DL 2126 LED-3500-930	25,4W	3434 lumens	135,2 lm/W	3000 K	90	B	D
DL 2126 LED-3500-940	25,4W	3629 lumens	142,9 lm/W	4000 K	90	B	D
DL 2126 LED 4000-830	34W	4275 lumens	158,3 lm/W	3000 K	80	B	D
DL 2126 LED 4000-840	34W	4500 lumens	166,6 lm/W	4000 K	80	B	D
DL 2126 LED 4000-930	31,7 W	4143 lumens	130,4 lm/W	3000 K	90	B	D
DL 2126 LED 4000-940	29,4 W	4139 lumens	140,6 lm/W	4000 K	90	B	D
DL 2126 LED 5000-830	43W	5075 lumens	118 lm/W	3000 K	80	B	D
DL 2126 LED 5000-840	43W	5350 lumens	124,4 lm/W	4000 K	80	B	D
DL 2126 LED 5500-930	41,8W	5262 lumens	125,9 lm/W	3000 K	90	B	D
DL 2126 LED 5500-940	41,8W	5592 lumens	133,8 lm/W	4000 K	90	B	D
DL 2126 LED 7500-830	55W	7325 lumens	133,1 lm/W	3000 K	80	A	D
DL 2126 LED 7500-840	55W	7700 lumens	140 lm/W	4000 K	80	A	D