

DL 2126 LED



DOWNLIGHTS ■ LED

- Circular recessed low luminance downlight for LED DOWNLIGHT module, maximum 7 700 lumens
- CRI of 80
- MacAdam Ellipse: 2 SDCM
- High output reflector, made of faceted anodized aluminium (FAC)
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 166,6 lm/W
- Springs in pressure for easier installation
- Housing and ring made of powder die-cast aluminium
- Static heat sink made of die-cast aluminium
- **Weight:** 1 kg
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD)

Driver(s)




Standards

Class I | IP 20 | 650°

Beam(s)



Dimensions



Colour(s)



Ø155 mm



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	BEAM	EFFICIENCY ENERGY CLASS
DL 2126 LED-3000-830	19W	21W	3025 lumens	144 lm/W	3000 K	80	B	D
DL 2126 LED-3000-840	19W	21W	3175 lumens	151,2 lm/W	4000 K	80	B	D
DL 2126 LED-4000-830	31W	34W	4275 lumens	158,3 lm/W	3000 K	80	B	D
DL 2126 LED-4000-840	31W	34W	4500 lumens	166,6 lm/W	4000 K	80	B	D
DL 2126 LED-5000-830	39W	43W	5075 lumens	118 lm/W	3000 K	80	B	D
DL 2126 LED-5000-840	39W	43W	5350 lumens	124,4 lm/W	4000 K	80	B	D
DL 2126 LED-7500-830	49W	55W	7325 lumens	133,1 lm/W	3000 K	80	A	D
DL 2126 LED-7500-840	49W	55W	7700 lumens	140 lm/W	4000 K	80	A	D