

■ LS 2476 LED



Colour(s)

RECESSED LUMINAIRES ■ LED

- Direct lighting system for CIRCULAR LED module, maximum 18 300 lumens
- CRI of 80
- MacAdam Ellipse : 3 SDCM
- Available in 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 124 lm/W
- Optical diffuser made of polymethyl methacrylate (PMMA)
- Extruded aluminum box painted
- **Weight** : 3 kg (Ø400mm), 5,9 kg (Ø600mm), 14,8 kg (Ø900mm), 23,8 kg (Ø1150mm)
- **Driver(s)** : Fixed, Dimmable DALI
- **Option(s)** : Suspension kit (KS), Transparent power cable and coat bracket suspension.


Driver(s)

Standards

Class I | IP20 | 650°

Beam(s)

Dimensions



ITEM	DIAMETER (MM)	POWER	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
LS 2476 LED 4000-830	400	36W	4090 lumens	91 lm/W	4 000 K	80	C
LS 2476 LED 8000-830	600	47W	7668 lumens	116 lm/W	4 000 K	80	C
LS 2476 LED 12000-830	900	68W	11212 lumens	117 lm/W	4 000 K	80	C
LS 2476 LED 18000-830	1150	105W	18300 lumens	124 lm/W	4 000 K	80	C

Option(s)

Power cable
1.5 m of cable
transparent 0.75 mm2

Suspension type "I"
(x3)

Central suspended
bracket