

## LS 2476 LED



### Colour(s)



## RECESSED LUMINAIRES ■ LED

- Direct lighting system for CIRCULAR LED module, maximum 18 300 lumens
- CRI of 80
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K
- 50 000 hours lamp life (L80B10)
  - Luminous efficiency of system up to 124 lm/W
- Optical diffuser made of polymethyl methacrylate (PMMA)
- Extruded aluminum box painted
- **Weight:** 3 kg (Ø400mm), 5,9 kg (Ø600mm), 14,8 kg (Ø900mm), 23,8 kg (Ø1150mm)
- **Convertisseur :** integrated
- **Option(s):** Dimmable driver DALI (CDIMMDALI), Suspension kit (KS), Transparent power cable and coat bracket suspension.

### Driver(s)




### Standards

Class I | IP20 | 650°

### Beam(s)



### Dimensions



ITEM	DIAMETER (MM)	POWER	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
LS 2476 LED 4000-830	400	36W	4090 lumens	91 lm/W	3000 K	80	C
LS 2476 LED 8000-830	600	47W	7668 lumens	116 lm/W	3000 K	80	C
LS 2476 LED 12000-830	900	68W	11212 lumens	117 lm/W	3000 K	80	C
LS 2476 LED 18000-830	1150	105W	18300 lumens	124 lm/W	3000 K	80	C

### Option(s)



Câble d'alimentation  
1,5 m de câble  
transparent 0,75 mm<sup>2</sup>



Suspension type «I»  
(x3)



Patère de suspension  
centrale