

PR 2220-B LED

LED PROJECTORS

- Orientable projector for LED SPOT module, maximum 3 875 lumens
- IRC de 80 or 90
- MacAdam Ellipse: 2 SDCM
- Available in 3 000 K or 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 145 lm/W
- 3-circuits track adaptor with integrated driver
- Head of spot made of die-cast aluminium
- Static heat sink
- Optical protection clear glass
- **Driver(s):** Fixed



Driver(s)





Standards

Class II | IP 20 | 650°

Beam(s)



Dimensions



ITEM	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
PR 2220-B LED 2000-930	14W	1918 lumens	137,9 lm/W	3000 K	90	D
PR 2220-B LED 2000-940	14W	2016 lumens	145 lm/W	4000 K	90	D
PR 2220-B LED 3000-830	22W	3025 lumens	137,5 lm/W	3000 K	80	D
PR 2220-B LED 3000-840	22W	3175 lumens	144 lm/W	4000 K	80	D
PR 2220-B LED-3500-930	25,4W	3434 lumens	135,2 lm/W	3000 K	90	D
PR 2220-B LED-3500-940	25,4W	3629 lumens	142,9 lm/W	4000 K	90	D
PR 2220-B LED 3800-830	28W	3700 lumens	132 lm/W	3000 K	80	D
PR 2220-B LED 3800-840	28W	3875 lumens	138 lm/W	4000 K	80	D