

# PR 2220-B LED

# LED PROJECTORS

- Orientable projector for LED SPOT module, maximum 3 875 lumens
- IRC de 80 ou 90
- MacAdam Ellipse: 2 SDCM
- Available in 2 700 K, 3 000 K or 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 144 lm/W
- 3-circuits track adaptor with integrated driver
- Head of spot made of die-cast aluminium
- Static heat sink
- Optical protection clear glass
- **Driver(s):** Fixed



## Driver(s)



## Standards

Class II | IP 20 | 650°



## Efficiency energy class



## Beam(s)



## Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
PR 2220-B LED 2500-927	19W	22W	2450 lumens	111,5 lm/W	2700 K	90
PR 2220-B LED 2500-930	19W	22W	2425 lumens	110 lm/W	3000 K	90
PR 2220-B LED 2500-940	19W	22W	2725 lumens	123,5 lm/W	4000 K	90
PR 2220-B LED 3000-927	25W	28W	3000 lumens	107 lm/W	2700 K	90
PR 2220-B LED 3000-930	25W	28W	2975 lumens	106 lm/W	3000 K	90
PR 2220-B LED 3000-940	25W	28W	3325 lumens	118,7 lm/W	4000 K	90
PR 2220-B LED 3000-830	19W	22W	3025 lumens	137,5 lm/W	3000 K	80
PR 2220-B LED 3000-840	19W	22W	3175 lumens	144 lm/W	4000 K	80
PR 2220-B LED 3800-830	25W	28W	3700 lumens	132 lm/W	3000 K	80
PR 2220-B LED 3800-840	25W	28W	3875 lumens	138 lm/W	4000 K	80