

AR 1528 LED



Colour(s)



HIGH BAY ■ LED

- High bay for LED SPOT module, maximum 6 133 lumens
- CRI of 90
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 143,5 lm/W
- Diffuser made of faceted aluminium
- Housing made of embossed aluminium
- Static heat sink
- **Weight:** approx. 4,4 kg
- **Included:** Suspension kit (KS)
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD), E27

Driver(s)



Standards

Class I | IP 20 | 650°


Efficiency energy class



Beam(s)



Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
AR 1528 LED-2000-930	13W	15,6W	1918 lumens	122,5 lm/W	3000 K	90
AR 1528 LED-2000-940	13W	15,6W	2049 lumens	131 lm/W	4000 K	90
AR 1528 LED-3000-930	21,5W	25,3W	2992 lumens	118,5 lm/W	3000 K	90
AR 1528 LED-3000-940	21,5W	25,3W	3196 lumens	126,5 lm/W	4000 K	90
AR 1528 LED-4000-830	23,3W	27,4W	3941 lumens	144 lm/W	3000 K	80
AR 1528 LED-4000-840	23,3W	27,4W	4043 lumens	147,5 lm/W	4000 K	80
AR 1528 LED-4000-930	30,4W	35W	3974 lumens	113,5 lm/W	3000 K	90
AR 1528 LED-4000-940	30,4W	35W	4246 lumens	121,5 lm/W	4000 K	90
AR 1528 LED-5000-830	30,4W	34,9W	4882 lumens	139,5 lm/W	3000 K	80
AR 1528 LED-5000-840	30,4W	34,9W	5008 lumens	143,5 lm/W	4000 K	80

Option(s)



E27