

# AR 5036-B LED

Grooved reflector



Smooth reflector



Colour(s)



## HIGH BAY ■ LED

- High bay for LED SPOT module, maximum 4 658 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 135,5 lm/W
- Housing made of embossed aluminium
- Static heat sink
- **Weight:** approx. 1,1 kg
- **Included:** Suspension kit (KS)
- **Driver:** No driver (230V)
- **Option(s):** Fast connector (CORD)
- Grooved or smooth reflector
- 3-circuit tracks
- **Photobiological risk group 0**

### Deported Driver(s)



### Standards

Class I | IP 20 | 650° | RG0



### Efficiency energy class



### Beam(s)



### Dimensions



ITEM	SECTION	DALI	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
AR 5036-B LED 2000-930	-	yes	14,9W	18,2W	2127 lumens	117 lm/W	3000 K	90
AR 5036-B LED 2000-940	-	yes	13,1W	16W	2055 lumens	128,5 lm/W	4000 K	90
AR 5036-B LED 3100-930	-	yes	23,7W	28,9W	3129 lumens	108,5 lm/W	3000 K	90
AR 5036-B LED 3400-940	-	yes	23,8W	29W	3377 lumens	116,5 lm/W	4000 K	90
AR 5036-B LED 3700-830	-	yes	23,8W	29W	3673 lumens	126,5 lm/W	3000 K	80
AR 5036-B LED 3900-840	-	yes	23,8W	29W	3932 lumens	135,5 lm/W	4000 K	80
AR 5036-B LED 3700-930	-	no	29,4W	34,6W	3705 lumens	107 lm/W	3000 K	90
AR 5036-B LED 4000-940	-	no	29,4W	34,6W	4000 lumens	115,5 lm/W	4000 K	90
AR 5036-B LED 4400-830	-	no	29,4W	34,6W	4351 lumens	126,5 lm/W	3000 K	80
AR 5036-B LED 4700-840	-	no	29,4W	34,6W	4658 lumens	134,5 lm/W	4000 K	80
AR 5036-B LED 2000-925-boulangerie	Bakery	yes	23,8W	29W	2086 lumens	72 lm/W	2500 K	90
AR 5036-B LED 2500-925-boulangerie	Bakery	no	29,4W	34,6W	2464 lumens	71 lm/W	2500 K	90
AR 5036-B LED 2000-930-boucherie	butchery	yes	23,8W	29W	2158 lumens	74,5 lm/W	3000 K	90
AR 5036-B LED 2500-930-boucherie	butchery	no	29,4W	34,6W	2548 lumens	73,5 lm/W	3000 K	90