

AR 5056-A LED



Colour(s)



Ø68 mm



HIGH BAY ■ LED

- High bay for LED SPOT module, maximum 3 932 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 3 SDCM
- Available in 2 500 K, 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 145,5 lm/W
- Housing and box made of die-cast painted aluminium
- Static heat sink
- **Weight:** approx. 0,9 kg
- **Driver(s):** No driver (230V)
- **Option(s) :** Opaline tube, length 1,5 m
- **Photobiological risk group 0**

Driver(s)

230V

Efficiency energy class

A+

Dimensions


Standards

Class I | IP 20 | 650° | RGO

Beam(s)



Hang collar
false ceiling



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
AR 5056-A LED 2000-925	23,8W	27W	2086 lumens	77 lm/W	2500 K	90
AR 5056-A LED 2000-930	23,8W	27W	2158 lumens	80 lm/W	3000 K	90
AR 5056-A LED 3100-930	23,7W	26,9W	3129 lumens	116 lm/W	3000 K	90
AR 5056-A LED 3400-940	23,8W	27W	3377 lumens	125 lm/W	4000 K	90
AR 5056-A LED 3700-830	23,8W	27W	3673 lumens	136 lm/W	3000 K	80
AR 5056-A LED 3900-840	23,8W	27W	3932 lumens	145,5 lm/W	4000 K	80

Option opaline tube

