

PR 2071 LED

LED PROJECTORS

- Orientable projector for LED SPOT module, maximum 4 700 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 2 SDCM
- Available in 2 700 K, 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 150 lm/W
- 3-circuits track adaptor with integrated driver
- Head of spot made of die-cast aluminium
- Static heat sink
- Optical protection clear glass
- **Weight:** approx. 1,1 kg
- **Driver(s) :** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s) :** Colour filters (FIL), food module




Driver(s)



Efficiency energy class



Dimensions



Standards

Class I | IP 20 | 650°

Beam(s)



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	BEAMS
PR 2071 LED 3000-927	31W	33W	3150 lumens	95,5 lm/W	2700 K	90	B
PR 2071 LED 3300-930	31W	33W	3300 lumens	100 lm/W	3000 K	90	B
PR 2071 LED 3500-830	25W	28W	3575 lumens	127,5 lm/W	3000 K	80	B
PR 2071 LED 3500-840	25W	28W	3675 lumens	131 lm/W	4000 K	80	B
PR 2071 LED 3500-940	31W	33W	3550 lumens	107,5 lm/W	4000 K	90	B
PR 2071 LED 4200-830	31W	33W	4175 lumens	126,5 lm/W	3000 K	80	B
PR 2071 LED 4200-840	31W	33W	4300 lumens	130,5 lm/W	4000 K	80	B
PR 2071 LED 4800-830	29W	32W	4650 lumens	145,5 lm/W	3000 K	80	A
PR 2071 LED 4800-840	29W	32W	4800 lumens	150 lm/W	4000 K	80	A