

# PR 2072 LED

# LED PROJECTORS



- Orientable projector for LED SPOT module, maximum 3 375 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 2 SDCM
- Available in 2 700 K, 3 000 K or 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 151 lm/W
- 3-circuits track adaptor with integrated driver
- Head of spot made of die-cast aluminium
- Static heat sink
- Optical protection clear glass
- **Weight:** approx. 0,7 kg
- **Driver(s):** Fixed
- **Option(s):** Colour filters (FIL)

### Driver(s)



### Standards

Class II | IP 20 | 650°


### Efficiency energy class



### Beam(s)



### Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
PR 2072 LED 2500-927	23W	25W	2475 lumens	99 lm/W	2700 K	90
PR 2072 LED 2500-930	23W	25W	2575 lumens	103 lm/W	3000 K	90
PR 2072 LED 2700-830	17W	18W	2625 lumens	146 lm/W	3000 K	80
PR 2072 LED 2700-840	17W	18W	2725 lumens	151 lm/W	4000 K	80
PR 2072 LED 2700-940	23W	25W	2775 lumens	111 lm/W	4000 K	90
PR 2072 LED 3300-830	23W	25W	3275 lumens	131 lm/W	3000 K	80
PR 2072 LED 3300-840	23W	25W	3375 lumens	135 lm/W	4000 K	80