

- Orientable projector for LED SPOT module, maximum 4 300 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 2 SDCM
- Available in 2 700 K, 3 000 K or 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 136 lm/W
- 3-circuits track adaptor with integrated driver
- Head of spot made of die-cast aluminium
- Static heat sink
- Optical protection clear glass
- **Weight:** approx. 0,5 kg
- **Driver(s):** Fixed
- **Option(s):** Colour filters (FIL)



Driver(s)



Standards

Class II | IP 20 | 650°



Efficiency energy class



Beam(s)



Dimensions



Colour(s)



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
PR 2074 LED 3000-927	31W	33W	3150 lumens	95,5 lm/W	2700 K	90
PR 2074 LED 3300-930	31W	33W	3300 lumens	100 lm/W	3000 K	90
PR 2074 LED 3500-830	25W	27W	3575 lumens	132,5 lm/W	3000 K	80
PR 2074 LED 3500-840	25W	27W	3675 lumens	136 lm/W	4000 K	80
PR 2074 LED 3500-940	31W	33W	3575 lumens	108,5 lm/W	4000 K	90
PR 2074 LED 4200-830	31W	33W	4200 lumens	127 lm/W	3000 K	80
PR 2074 LED 4200-840	31W	33W	4300 lumens	130,5 lm/W	4000 K	80