

PR 2033-B LED

- » Orientable projector for LED SPOT module, maximum 3 200 lumens
- » High quality of light with a CRI up to 90
- » Available in 3000 K and 4000 K
- » 50 000 hours life expectancy (L80B50)
- » 3-circuits track adaptor
- » Luminous efficiency of system up to 128 lm/W
- » Housing and box made of painted die-cast aluminium
- » Static heat sink
- » Optical protection clear glass

- » **Adjustable:** 80° and Turnable: 360°
- » **Colour(s):** White (WH), Grey (GR), Black (BK)
- » **Driver(s):** Fixed (C Fixed), dimmable driver DALI (C DIMMDALI)
- » **Option(s):** Colour filters (FIL)



Driver(s)



Beam(s)





Colour(s)



Standards

Class I | IP 20 | 650°

Efficiency energy class



LED SPOT MODULE

ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR T°	CRI
PR 2033-B LED 2700-930	25W	28W	2850 lumens	102 lm/W	3000 K	90
PR 2033-B LED 2700-940	22W	26W	2900 lumens	111,5 lm/W	4000 K	90
PR 2033-B LED 3000-830	21W	25W	3140 lumens	125,5 lm/W	3000 K	80
PR 2033-B LED 3000-840	21W	25W	3200 lumens	128 lm/W	4000 K	80

OPTION(S)



FIL