

RB 2328 LED WHITE IPOO

BATTEN LUMINAIRES / LED FLEX ■ LED

- LED FLEX IP 00, 24 volts, maximum 2470 lumens / meter (beyond, contact us)
- CRI of 80 or 90
- MacAdam Ellipse: 3 SDCM
- Available in 2700 K, 3000 K, 4000 K or 6500 K (others, consult us)
- Up to 50 000 hours lamp life
- Luminous efficiency of system up to 142 lm/W
- 3M self-adhesive led flex for easier installation
- **Weight:** Approx. 0,5 kg
- **Length(s):** Led flex total length 4800 mm, divisible every 50 or 100 mm
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI), 1-10 V Driver (1-10V)



Driver(s)



Standards

Class III | IP 00 | 650°

Efficiency energy class



Beam(s)



Dimensions



	ITEM	CONSUMPTION (WATT/METER)	LUMINOUS FLUX (LUMENS/METER)	EFFICIENCY (LM/W)	COLOUR TEMPERATURE	CRI	LENGTH (MM)	CUTTING (MM)	PITCH
EMPHASIZE	RB 2328 LED 600-827	3,8 W/m	520 Lm/m	136 Lm/W	2700 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 600-830	3,8 W/m	520 Lm/m	136 Lm/W	3000 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 600-840	3,8 W/m	520 Lm/m	136 Lm/W	4000 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 600-865	3,8 W/m	520 Lm/m	136 Lm/W	6500 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 600-927	6,2 W/m	600 Lm/m	97 Lm/W	2700 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 600-930	6,2 W/m	600 Lm/m	97 Lm/W	3000 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 600-940	5,6 W/m	615 Lm/m	110 Lm/W	4000 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 600-965	5,6 W/m	615 Lm/m	110 Lm/W	6500 K	90	4800 mm	50 mm	7 mm
DECORATE	RB 2328 LED 1200-827	7,8 W/m	1050 Lm/m	135 Lm/W	2700 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1200-830	7,4 W/m	1050 Lm/m	142 Lm/W	3000 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1200-840	7,4 W/m	1050 Lm/m	142 Lm/W	4000 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1200-865	8,9 W/m	1020 Lm/m	115 Lm/W	6500 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1200-927	11,2 W/m	1190 Lm/m	106 Lm/W	2700 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 1200-930	11,2 W/m	1190 Lm/m	106 Lm/W	3000 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 1200-940	10,8 W/m	1220 Lm/m	113 Lm/W	4000 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 1200-965	10,8 W/m	1220 Lm/m	113 Lm/W	6500 K	90	4800 mm	50 mm	7 mm
LIGHT	RB 2328 LED 1800-827	11,8 W/m	1550 Lm/m	131 Lm/W	2700 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1800-830	11,8 W/m	1550 Lm/m	131 Lm/W	3000 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1800-840	11,3 W/m	1550 Lm/m	137 Lm/W	4000 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1800-865	11,3 W/m	1550 Lm/m	137 Lm/W	6500 K	80	4800 mm	100 mm	14 mm
	RB 2328 LED 1800-927	18 W/m	1770 Lm/m	98 Lm/W	2700 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 1800-930	18 W/m	1770 Lm/m	98 Lm/W	3000 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 1800-940	15,8 W/m	1780 Lm/m	113 Lm/W	4000 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 1800-965	15,8 W/m	1780 Lm/m	113 Lm/W	6500 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 2500-927	26 W/m	2470 Lm/m	95 Lm/W	2700 K	90	4800 mm	50 mm	7 mm
	RB 2328 LED 2500-930	27 W/m	2470 Lm/m	95 Lm/W	3000 K	90	4800 mm	50 mm	7 mm
RB 2328 LED 2500-940	22,6 W/m	2440 Lm/m	108 Lm/W	4000 K	90	4800 mm	50 mm	7 mm	
RB 2328 LED 2500-965	22,6 W/m	2440 Lm/m	108	6500 K	90	4800 mm	50 mm	7 mm	