

EO 2181 LED



Colour(s)



Ø150 mm



ORIENTABLE AND ADJUSTABLE ■ LED

- Circular recessed orientable spotlight for LED SPOT module, maximum 4 525 lumens
- CRI of 80 or 90
- MacAdam Ellipse : 2 SDCM
- Available in 3 000 K ou 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 145 lm/W
- Springs in pressure for easier installation
- Static heat sink
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDA LI)

Driver(s)




Standards

Class II | IP 20 | 650°

Beam(s)



Dimensions



ITEM	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
EO 2181 LED-2000-930	14W	1918 lumens	137,9 lm/W	3000 K	90	D
EO 2181 LED-2000-940	14W	2016 lumens	145 lm/W	4000 K	90	D
EO 2181 LED 3000-830	21W	2950 lumens	140,5 lm/W	3000 K	80	D
EO 2181 LED 3000-840	21W	3025 lumens	144 lm/W	4000 K	80	D
EO 2181 LED 3500-830	27W	3600 lumens	133,3 lm/W	3000 K	80	D
EO 2181 LED 3500-840	27W	3700 lumens	137 lm/W	4000 K	80	D
EO 2181 LED 3500-930	25,4W	3434 lumens	135,2 lm/W	3000 K	90	D
EO 2181 LED-3500-940	25,4W	3629 lumens	142,9 lm/W	4000 K	90	D
EO 2181 LED 4000-930	31,7 W	4143 lumens	130,4 lm/W	3000 K	90	D
EO 2181 LED 4000-940	29,4 W	4139 lumens	140,6 lm/W	4000 K	90	D
EO 2181 LED 4500-830	35W	4425 lumens	126,4 lm/W	3000 K	80	D
EO 2181 LED 4500-840	35W	4525 lumens	129,3 lm/W	4000 K	80	D