

## LE 2316-B LED

## RECESSED LUMINAIRES ■ LED

- Recessed luminaire for LINEAR LED module, maximum 8367 lumens
- CRI of 80
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K, 4 000 K and 6 500 K
- 50 000 hours lamp life (L80B20)
- Luminous efficiency of system up to 113,5 lm/W
- Micro prismatic Diffuser
- Lay-in (LI)
- Housing made of painted steel
- Static heat sink
- UGR < 19
- **Weight:** approx. 5,6 kg
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s):** IP 65 built-in frame, Ready-to-mount kit (security wire, protection film) (KC)

### Driver(s)



### Standards

Class II | IP 40 | 650°

### Efficiency energy class




### Beam(s)



### Dimensions

LI



### Colour(s)



ITEM	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
LE 2316-B LED-5000-830	47,1W	5000 lumens	106,1 lm/W	3000 K	80
LE 2316-B LED-7800-830	78,5W	7816 lumens	99,6 lm/W	3000 K	80
LE 2316-B LED-5300-840	47,1W	5350 lumens	113,5 lm/W	4000 K	80
LE 2316-B LED-8300-840	78,5W	8367 lumens	106,6 lm/W	4000 K	80
LE 2316-B LED-5300-865	47,1W	5350 lumens	113,5 lm/W	6500 K	80
LE 2316-B LED-8300-865	78,5W	8367 lumens	106,6 lm/W	6500 K	80