

DL 2583 LED



Colour(s)



Ø62 mm



DOWNLIGHTS ■ LED

- Circular recessed downlight for LED DOWNLIGHT module, maximum 960 lumens
- CRI of 90
- MacAdam Ellipse : 3 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B20)
- Luminous efficiency of system up to 142 lm/W
- Springs in pressure for easier installation
- White matt aluminium reflector
- Static heat sink
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s) :** IP54 bezel (underside)

Driver(s)




Standards

Class II | IP 20 | 650°

Beam(s)



Dimensions



ITEM	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
DL 2583 LED 700-930	5W	700 lumens	140 lm/W	3000 K	90	E
DL 2583 LED 700-940	5W	710 lumens	142 lm/W	4000 K	90	E
DL 2583 LED 1000-930	7W	940 lumens	134,9 lm/W	3000 K	90	E
DL 2583 LED 1000-940	7W	960 lumens	137,1 lm/W	4000 K	90	E