

LE 2476 LED



RECESSED LUMINAIRES ■ LED

- Direct lighting system for CIRCULAR LED module, maximum 18 300 lumens
- CRI of 80
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 124 lm/W
- Optical diffuser made of polymethyl methacrylate (PMMA)
- Extruded aluminum box painted
- Housing made of painted steel
- Stretcher attachment system
- **Weight** 3,5 kg (Ø400mm), 6,9 kg (Ø600mm), 15,8 kg (Ø900mm), 25,4 kg (Ø1150mm)
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Suspension kit (KS), Transparent power cable and coat bracket suspension.


Colour(s)



Dimensions


92 mm

Ø400




Ø381 mm

Ø600




Ø581 mm

Ø900



Ø881 mm

Ø1150



Ø1131 mm

ITEM	DIAMETER (MM)	POWER	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
LE 2476 LED 4000-830	400	36W	4090 lumens	91 lm/W	3000 K	80	C
LE 2476 LED 8000-830	600	47W	7668 lumens	116 lm/W	3000 K	80	C
LE 2476 LED 12000-830	900	68W	11212 lumens	117 lm/W	3000 K	80	C
LE 2476 LED 18000-830	1150	105W	18300 lumens	124 lm/W	3000 K	80	C

Option(s)



Power cable
1.5 m of cable
transparent 0.75 mm2



Suspension type "I"
(x3)



Central suspended
bracket

Driver(s)



Standards

Class I | IP20 | 650°

Beam(s)

