

# LE 2476 LED



# RECESSED LUMINAIRES ■ LED

- Direct lighting system for CIRCULAR LED module, maximum 18 300 lumens
- CRI of 80
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 124 lm/W
- Optical diffuser made of polymethyl methacrylate (PMMA)
- Extruded aluminum box painted
- Housing made of painted steel
- Stretcher attachment system
- **Weight** 3,5 kg (Ø400mm), 6,9 kg (Ø600mm), 15,8 kg (Ø900mm), 25,4 kg (Ø1150mm)
- **Driver(s):** intégré
- **Option(s):** Dimmable driver DALI (CDIMMDALI), Kit de suspension, Transparent power cable and coat bracket suspension.

### Driver(s)



### Standards

Class I | IP20 | 650°

### Efficiency energy class



### Beam(s)





### Colour(s)





### Dimensions





Ø400




Ø600



Ø900



Ø1150



ITEM	DIAMETER (MM)	POWER	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
LE 2476 LED 4000-830	400	36W	4090 lumens	91 lm/W	3000 K	80
LE 2476 LED 8000-830	600	47W	7668 lumens	116 lm/W	3000 K	80
LE 2476 LED 12000-830	900	68W	11212 lumens	117 lm/W	3000 K	80
LE 2476 LED 18000-830	1150	105W	18300 lumens	124 lm/W	3000 K	80

### Option(s)



Power cable  
1.5 m of cable  
transparent 0.75 mm<sup>2</sup>



Suspension type "I"  
(x3)



Central suspended  
bracket