










DL 2820 LED 2W

DL 2820 LED 6W

DL 2820 LED 10W

DL 2820 LED 20W



Colour(s)



## DL 2820 LED

- Recessed luminaire for LINEAR LED module, maximum 2100 lumens
- CRI of 90
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 105 lm/W
- Optic composed of a lens and an individual reflector for each module
- Housing made of painted steel
- Static heat sink
- **Weight:** approx. 0,05 kg
- **Driver(s):** Fixe, Fixed, Dimmable driver DALI (CDIMMDALI)

### Driver(s)



### Beam(s)



### Standards

Class III | IP 20 | 650°

### Efficiency energy class



ITEM	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
DL 2820 LED-210-930	2W	210 lumens	105 lm/W	3000 K	90
DL 2820 LED-630-930	6W	630 lumens	105 lm/W	3000 K	90
DL 2820 LED-1000-930	10W	1050 lumens	105 lm/W	3000 K	90
DL 2820 LED-2100-930	20W	2100 lumens	105 lm/W	3000 K	90