


LS 2316-A LED



Colour(s)



TRACK SUSPENDED LUMINAIRE

- Track suspended luminaire for LINEAR LED module, maximum 4357 lumens
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K, 4 000 K and 6 500 K
- 50 000 hours lamp life (L70B50)
- Luminous efficiency of system up to 106 lm/W
- Opal Diffuser (DO)
- Housing made of painted steel
- Static heat sink
- **Weight:** approx. 2,6 Kg
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)

Driver(s)



Standards

Class I | IP 20 | 650°


Efficiency energy class



Beam(s)



Dimensions



ITEM	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
LS 2316-A LED-3200-830	32W	3220 lumens	100 lm/W	3000 K	80
LS 2316-A LED-4100-830	43W	4125 lumens	96 lm/W	3000 K	80
LS 2316-A LED-3400-840	32W	3400 lumens	106 lm/W	4000 K	80
LS 2316-A LED-4300-840	43W	4357 lumens	101 lm/W	4000 K	80
LS 2316-A LED-3400-865	32W	3400 lumens	106 lm/W	6500 K	80
LS 2316-A LED-4300-865	43W	4357 lumens	101 lm/W	6500 K	80