

LS 5148 LED



Colour(s)



SUSPENDED LUMINAIRES ■ LED

- Suspended luminaire for LED module, maximum 7 700 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 2 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 166,6 lm/W
- Housing made of aluminium
- Static heat sink
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD)

Driver(s)




Standards

Class I | IP 20 | 650°

Beam(s)



Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	BEAM	EFFICIENCY ENERGY CLASS
LS 5148 LED 3000-830	19W	21W	3025 lumens	144 lm/W	3000 K	80	B	D
LS 5148 LED 3000-840	19W	21W	3175 lumens	151,2 lm/W	4000 K	80	B	D
LS 5148 LED 4000-830	25W	27W	4275 lumens	158,3 lm/W	3000 K	80	B	D
LS 5148 LED 4000-840	25W	27W	4500 lumens	166,6 lm/W	4000 K	80	B	D
LS 5148 LED 5000-830	39W	43W	5075 lumens	118 lm/W	3000 K	80	B	D
LS 5148 LED 5000-840	39W	43W	5350 lumens	124,4 lm/W	4000 K	80	B	D
LS 5148 LED 6000-930	49W	55W	6075 lumens	110,5 lm/W	3000 K	90	A	D
LS 5148 LED 6000-940	49W	55W	6600 lumens	120 lm/W	4000 K	90	A	D
LS 5148 LED 7500-830	49W	55W	7325 lumens	133,1 lm/W	3000 K	80	A	D
LS 5148 LED 7500-840	49W	55W	7700 lumens	140 lm/W	4000 K	80	A	D