

ET 2481-C LED



Coulour(s)



EXTRA PROTECTED LUMINAIRES ■ LED

- Tubular LED luminaire Waterproof IP68 for LINEAR MODULE maximum 4038 lumens
- CRI of 80
- MacAdam Ellipse: 3 SDCM
- Available in 4 000 K
- 80 000 hours lamp life (L90B10)
- Luminous efficiency of system up to 144 lm/W
- Opale diffuser
- Made of Ø72mm transparent or opal polycarbonate tube, with inner aluminium profile and injected transparent polycarbonate end caps.
- Static heat sink
- Dust and waterproof optical compartment (IP 68)
- For ceiling surface mounted or suspended and wall mounted application
- **Standard body lengths:** 620 mm, 900 mm, 1180 mm, 1460 mm
- **Weight:** approx. 1,4 Kg (620 mm), 1,8 Kg (900 mm), 2,1 Kg (1180 mm), 2,4 Kg (1460 mm)

Driver(s)



Standards

Class II | IP 68 | IK 10 | 650°


Efficiency energy class



Beam(s)



Dimensions



ITEM	LENGHT	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI
ET 2481-C LED 1600-840	620 mm	13W	1596 lumens	123 lm/W	4000 K	80
ET 2481-C LED 2400-840	900 mm	18W	2394 lumens	133 lm/W	4000 K	80
ET 2481-C LED 3200-840	1180 mm	23W	3192 lumens	139 lm/W	4000 K	80
ET 2481-C LED 4000-840	1460 mm	28W	4038 lumens	144 lm/W	4000 K	80