

LS 5158 LED



SUSPENDED LUMINAIRES ■ LED

- Suspended luminaire for LINEAR LED module, maximum 13 968 lumens
- CRI of 80
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B20)
- Luminous efficiency of system up to 173,6 lm/W
- Housing made of painted steel
- Static heat sink
- **Weight:** approx. 50 kg
- **Driver(s):** C Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD)

Driver(s)



Standards

Class I | IP 20 | 650°

Beam(s)



Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
LS 5158 LED 4800-830	26,3W	29,6W	5094 lumens	171,9 lm/W	3000 K	80	C
LS 5158 LED 5000-840	31W	34,8W	5310 lumens	152,6 lm/W	4000 K	80	C
LS 5158 LED 8000-830	45W	54,9W	8406 lumens	153,2 lm/W	3000 K	80	C
LS 5158 LED 8000-840	50,1W	61W	8670 lumens	142 lm/W	4000 K	80	C
LS 5158 LED 13000-830	72W	84W	13 968 lumens	166 lm/W	3000 K	80	C
LS 5158 LED 13000-840	66,3W	77,1W	13 392 lumens	173,6 lm/W	4000 K	80	C