

■ LS 5121-F LED



Colour(s)

WALL WASHERS LED

- Track suspended luminaire for LINEAR LED module(s), maximum 4 378 lumens
- CRI of 80
- MacAdam Ellipse : 3 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 168,5 lm/W
- Optic composed of a lens and an individual reflector for each module
- 3 circuits track adaptor
- Housing made of prelacquered steel
- Static heat sink
- **Standard body length** : 300 mm
- **Driver(s)** : Fixed, Dimmable DALI (CDIMMDALI), Casambi, Connect
- **Option** : Version for 48V rail

Driver(s)

FIXE

C
DIMM
DALI

CASAMBI

CONNECT

Standards

Class I | IP 20 | 650°

Beam(s)

Dimensions

640 mm / 1280 mm

43 mm 30 mm

ITEM	LENGTH	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	EFFICIENCY ENERGY CLASS
LS 5121-F LED - 2200-830	640 mm	16,3W	2259 lumens	138,6 lm/W	3000 K	80	C
LS 5121-F LED - 2200-840	640 mm	16,3W	2364 lumens	145 lm/W	4000 K	80	C
LS 5121-F LED - 4200-830	1280 mm	26W	4184 lumens	161,1 lm/W	3000 K	80	C
LS 5121-F LED - 4200-840	1280 mm	26W	4378 lumens	168,5 lm/W	4000 K	80	C

*Configuration can be arranged upon request.